C.A.M.S.

Antique Tractor Transfer (Western Style) Pull Rules and Regulations

Tractors 1959 and older or production models that started in 1959

3000 - 8000lbs in 500lb Increments

\$15.00 Hook Fee

1. You Must be a C.A.M.S. Member to Pull!

- 2. All tractors must be in production before 1959!
 - a. Allis Chalmers D15, D17, D19 or any older model.
 - **b.** Case 600, 700, 800 or any older model.
 - c. Ferguson any model.
 - **d.** Ford 681, 881 or any older model.
 - e. International 340, 460, 560 or any older model.
 - **f.** John Deere all two cylinder models.
 - **g.** Massy Ferguson 30, 50, 65, 85.
 - **h.** Massy Harris any model.
 - i. Minneapolis Moline 4 Star, 5 Star or any older model.
 - *j.* Oliver 660, 770, 880 or any older model
- 3. <u>Tractors may be entered in 2 classes max, but only once in each CLASS. Sign in and scales open 8:00am.</u>
 Start time 9:00am. You must be signed in before the class starts. NO REFUNDS!
- **4.** No tractor equipped with dual wheels, four wheel drive or chains permitted. (Steel wheels and crawlers are encouraged if within year.)
- **5.** An Insurance Release Form must be signed before pulling onto the scales.
- 6. Weight will include driver. No weight or driver changes permitted after weigh in. All weights will be of factory manufacture. No weight will interfere with hookup of sled. A minimum of 12 inches square shall be open around the drawbar.
- 7. All suitcase weights must be on a satisfactory bracket and be secured so that they are safe and do not rattle or flop around. All round wheel weights shall be bolted into place and can only be used on the axle and wheels, unless they are secured on a bracket. No loose or chained weights will be permitted. No weight shall extend more than 12 inches past the trailing edge of the rear tires and can't be more than 11 feet from the center of the rear axle to the furthest point forward. Any weights, that by the discretion of the judge are, unsafe or unsecured will be removed or the tractor will not be permitted to compete.
- 8. Drawbar height will be a maximum of 18 inches from ground. All manufactured drawbars must be RIGID with no vertical free float. All OEM drawbars will be at the Judge's Discretions if it within the requirements. Pulling rings will be accepted. Must have two bolts no less than ½" in diameter and no less than grade 5.This will be checked on the scales. C.A.M.S. reserves the right to re-weigh your tractor and/or check your drawbar height at any time. If there is no ring a pin and clevis should be used. If there is not one, then one will be provided.
- 9. Maximum tire size: 2000lb 6000lb classes 15.5 38 and under. 6500lb 8000lb classes 16.9 38 and under. NO CUT, ALTERED, OR SHARPENED TIRES!!! Any tire or rim in question will be allowed or rejected by at least two people from the track officials.
- 10. Any gear is allowed, however, there will be a 3.5 mph limit. There is a ONE horn warning for speeding. If 2nd horn sounds or if the horn is blowing continually with no indication of the driver slowing down he will be flagged and disqualified! Any questions or problems that arise will be handled by the track officials.
- 11. Track Officials have the right to stop any contestant's tractor at anytime when being operated in an unsafe manner. Judge's decision is final. No Alcohol on the grounds. This is grounds for Disqualification from the event.